Learning in the 706r to an i-on

Compatibility

i-on Control Panel software must be Any version.
Note: PA (HUA) and the "Man Down" (tilt) will both be seen as PA (HUA).

Learning in the 706r to an i-on

The 706r is learnt into **user code positions** as follows: -

Clear all faults on the system and escape from the Installer menu (Press the X button unit till you see *"Leave installer mode?"* displayed then press **TICK**.

Press the menu button (top right) and enter the User 01 code and go to: -

USER MENU – Users – Add User – User 00?: -

Normal User **PRESS TICK**

Assign Access Code ( ) if no code is required **PRESS TICK**

Present Prox Tag to add to panel if no Prox Tag is required **PRESS TICK**

Press button to identify Remote if no Remote is required **PRESS TICK**

Press button to identify Social Care Pendent if no Pendent is required **PRESS TICK**

Press button to identify Medical Pendent if no Pendent is required **PRESS TICK**

Press both buttons to identify HUD **PRESS BOTH SIDE BUTTONS ON THE 706r**

SET REM. PASSWORD if no Remote Password is required **PRESS TICK**

"**New user added**" will be displayed

Operation

The two side buttons when pushed together = a PA (HUA).

The “Man down (tilt) will also be seen as a PA (HUA).

Please note the above is not an official Eaton Security Document but has been written as an aid-memoir for the author. The information is believed to be correct but as with all programming and set-ups the system should be tested on site to ensure correct operation. This document may be subject to change without notification. Please feel free to report any errors or omissions. MR 23-03-23.